

Technische gegevens

	Q [m³/h]	ΔP [Pa]	ti [C°]	Tw 80°/60°C				Tw 60°/40°C				Tw 55°/45°C			
				tu [C°]	P [kW]	Qw [l/s]	ΔPw [kPa]	tu [C°]	P [kW]	Qw [l/s]	ΔPw [kPa]	tu [C°]	P [kW]	Qw [l/s]	ΔPw [kPa]
CWW-H-D 100-2,5	55	6	-15	40.1	1.2	0.01	0.4	22.7	0.8	0.01	0.2	27.8	0.9	0.02	1
		6	-7.5	42.7	1	0.01	0.4	25.9	0.7	0.01	0.2	30.3	0.8	0.02	0.8
		6	0	45	0.9	0.01	0.3	29.1	0.6	0.01	0.1	32.6	0.6	0.02	0.6
		6	7.5	47	0.8	0.01	0.2	32.1	0.5	0.01	0.1	34.6	0.5	0.01	0.4
	100	6	15	48.9	0.6	0.01	0.1	35.1	0.4	0.01	0.1	36.6	0.4	0.01	0.2
		15	-15	30.2	1.7	0.02	0.9	15.9	1.2	0.01	0.5	20.3	1.3	0.03	2.2
		15	-7.5	33.7	1.5	0.02	0.7	18.8	1	0.01	0.3	23.7	1.2	0.03	1.7
		15	0	37.1	1.3	0.02	0.6	22.1	0.8	0.01	0.2	27	1	0.02	1.2
	145	14	7.5	40.3	1.2	0.01	0.4	26.1	0.7	0.01	0.2	30.1	0.8	0.02	0.8
		14	15	43.3	1	0.01	0.3	30	0.5	0.01	0.1	33	0.6	0.02	0.5
		30	-15	24.2	2.2	0.03	1.5	12	1.5	0.02	0.7	15.7	1.7	0.04	3.5
		29	-7.5	28.3	1.9	0.02	1.2	15.7	1.3	0.02	0.5	19.7	1.5	0.04	2.6
CWW-H-D 100-3,2,5	55	28	0	32.3	1.7	0.02	0.9	19	1	0.01	0.3	23.6	1.2	0.03	1.9
		27	7.5	36.1	1.5	0.02	0.7	22.8	0.8	0.01	0.2	27.3	1	0.02	1.3
		26	15	39.7	1.2	0.02	0.5	27.3	0.6	0.01	0.1	30.8	0.8	0.02	0.8
		9	-15	57.1	1.5	0.02	1.1	37.1	1.1	0.01	0.6	39.9	1.2	0.03	2.5
	100	9	-7.5	58.5	1.3	0.02	0.9	38.1	0.9	0.01	0.4	41.2	1	0.02	1.9
		9	0	59.7	1.2	0.01	0.7	39.2	0.8	0.01	0.3	42.4	0.8	0.02	1.4
		9	7.5	60.8	1	0.01	0.5	40.9	0.6	0.01	0.2	43.4	0.7	0.02	1.0
		9	15	61.6	0.9	0.01	0.4	42.5	0.5	0.01	0.2	44.2	0.6	0.01	0.6
	145	23	-15	46.9	2.4	0.03	2.6	29.9	1.7	0.02	1.4	32.5	1.8	0.04	6
		23	-7.5	49.2	2.1	0.03	2.1	31.9	1.5	0.02	1	34.7	1.6	0.04	4.5
		22	0	51.4	1.9	0.02	1.6	33.6	1.2	0.01	0.7	36.8	1.3	0.03	0.3
		21	7.5	53.4	1.6	0.02	1.2	34.8	1	0.01	0.5	38.7	1.1	0.03	2.3
CWW-H-D 125-2,5	85	21	15	55.3	1.4	0.02	0.9	36.7	0.7	0.01	0.3	40.4	0.9	0.02	1.5
		45	-15	40.2	3.1	0.04	4.2	25	2.2	0.03	2.3	27.5	2.4	0.06	9.9
		43	-7.5	43.1	2.7	0.03	3.4	27.6	1.9	0.02	1.7	303	2	0.05	7.4
		42	0	45.9	2.4	0.03	2.7	30.1	1.6	0.02	1.2	32.9	1.7	0.04	5.4
	150	40	7.5	48.5	2.1	0.03	2	32.2	1.3	0.02	0.8	35.4	1.4	0.03	3.7
		39	15	51	1.8	0.02	1.5	33.8	0.9	0.01	0.5	37.8	1.1	0.03	2.4
		12	-15	32.9	1.6	0.02	0.8	17.5	1.1	0.01	0.4	22.3	1.2	0.03	1.8
		11	-7.5	36.2	1.4	0.02	0.6	20.4	0.9	0.01	0.3	25.5	1	0.03	1.4
	215	11	0	39.3	1.2	0.01	0.5	23.9	0.7	0.01	0.2	28.5	0.9	0.02	1
		11	7.5	42.2	1	0.01	0.4	27.6	0.6	0.01	0.1	31.4	0.7	0.02	0.7
		11	15	44.8	0.9	0.01	0.3	31.3	0.5	0.01	0.1	33.9	0.6	0.01	0.4
		31	-15	23.7	2.2	0.03	1.5	11.7	1.5	0.02	0.8	15.3	1.7	0.04	3.7
CWW-H-D 125-3,2,5	85	30	-7.5	27.9	2	0.02	1.2	15.4	1.3	0.02	0.5	19.4	1.5	0.04	2.7
		29	0	31.9	1.7	0.02	0.9	18.8	1	0.01	0.4	23.3	1.3	0.03	2
		28	7.5	35.7	1.5	0.02	0.7	22.5	0.8	0.01	0.2	27	1	0.03	1.3
		28	15	39.4	1.3	0.02	0.5	27.1	0.6	0.01	0.1	30.6	0.8	0.02	0.8
	150	61	-15	18.3	2.7	0.03	2.3	8.1	1.9	0.02	1.1	11.2	2.2	0.05	5.5
		59	-7.5	22.9	2.4	0.03	1.8	12.4	1.6	0.02	0.8	15.7	1.9	0.04	4.1
		58	0	27.5	2.1	0.03	1.4	16.5	1.3	0.02	0.5	20.1	1.6	0.04	3
		56	7.5	31.8	1.8	0.02	1.1	20.2	1	0.01	0.3	24.4	1.3	0.03	2
	215	54	15	36.1	1.6	0.02	0.8	24.8	0.7	0.01	0.2	28.5	1	0.02	1.3
		6	-15	66.9	2.7	0.03	5.7	47.3	2	0.02	3.5	46.4	2	0.05	12.6
		5	-7.5	67.8	2.4	0.03	4.6	48	1.8	0.02	2.7	47.2	1.7	0.04	9.6
		5	0	68.6	2.1	0.03	3.7	48.6	1.5	0.02	2	48	1.5	0.04	7.1
CWW-H-D 160-2,5	85	5	7.5	69.3	1.8	0.02	2.9	49	1.2	0.02	1.4	48.7	1.2	0.03	5
		5	15	69.9	1.6	0.02	2.2	49	1	0.01	0.9	49.2	1	0.02	3.4
		12	-15	58.4	4.2	0.05	13.7	40.5	3.2	0.04	8.2	40.4	3.2	0.08	30.6
		12	-7.5	60.1	3.8	0.05	11	42	2.8	0.03	6.3	41.9	2.8	0.07	23.3
	150	11	0	61.6	3.3	0.04	8.8	43.3	2.3	0.03	4.6	43.3	2.3	0.06	17.2
		11	7.5	63	2.9	0.04	3.8	44.4	1.9	0.02	3.2	44.7	2	0.05	12.2
		11	15	64.2	2.5	0.03	5.2	45.3	1.6	0.02	2.1	45.9	1.6	0.04	8.2
		20	-15	52.2	5.5	0.07	22.9	35.6	4.2	0.05	13.7	35.9	4.2	0.1	51.8
	215	20	-7.5	54.4	4.9	0.06	18.5	37.6	3.6	0.04	10.4	37.9	3.6	0.09	39.5
		19	0	56.4	4.4	0.05	14.7	39.5	3.1	0.04	7.6	39.9	3.1	0.08	29.1
		19	7.5	58.3	3.8	0.05	11.5	41.1	2.5	0.03	5.4	41.7	2.6	0.06	20.6
		18	15	60.1	3.3	0.04	8.7	42.6	2	0.02	3.5	43.3	2.1	0.05	13.8
CWW-H-D 160-3,2,5	145	7	-15	43.2	3.2	0.04	5.5	28.1	2.4	0.03	3.2	29.4	2.5	0.06	12.6
		7	-7.5	46.1	2.9	0.04	4.4	30.8	2.1	0.03	2.4	32.1	2.1	0.05	9.6
		7	0	48.8	2.6	0.03	3.5	33.2	1.7	0.02	1.8	34.7	1.8	0.04	7.1
		7	7.5	51.3	2.2	0.03	2.7	35.4	1.4	0.02	1.2	37.1	1.5	0.04	5
	250	6	15	53.7	1.9	0.02	2.1	37.2	1.1	0.01	0.8	39.4	1.2	0.03	3.3
		16	-15	33.5	4.6	0.06	10.9	20.8	3.4	0.04	6.3	22.1	3.5	0.09	25.2
		16	-7.5	37.1	4.1	0.05	8.8	24.3	2.9	0.04	4.7	25.7	3.1	0.07	19.2
		15	0	40.6	3.7	0.05	7	27.6	2.5	0.03	3.5	29.1	2.6	0.06	14.2
	355	15	7.5	44	3.2	0.04	5.4	30.7	2	0.02	2.4	32.3	2.2	0.05	10
		15	15	47.3	2.8	0.03	4.1	33.6	1.6	0.02	1.5	35.5	1.8	0.04	6.6
		30	-15	27.4	5.8	0.07	16.6	16.3	4.2	0.05	9.5	17.6	4.4	0.11	38.4
		29	-7.5	31.6	5.2	0.06	13.4	20.3	3.7	0.04	7.2	21.6	3.8	0.09	29.3
CWW-H-D 160-3,2,5	145	29	0	35.6	4.6	0.06	10.7	24.1	3.1	0.04	5.2	25.5	3.3	0.08	21.6
		28	7.5	39.5	4	0.05	8.3	27.8	2.5	0.03	3.6	29.3	2.7	0.07	15.3
		27	15	43.3	3.4	0.04	6.2	31.3	2	0.02	2.2	33	2.2	0.05	10
		11	-15	59	4.1	0.05	13	41	3.1	0.04	7.8	40.8	3.1	0.08	29.1
	250	11	-7.5	60.6	3.7	0.05	10.5	42.4	2.7	0.03	6	42.3	2.7	0.07	22.1
		10	0	62	3.2	0.04	8.3	43.6	2.3	0.03	4.4	43.7	2.3	0.06	16.4
		10	7.5	63.4	2.8	0.04	6.5	44.7	1.9	0.02	3.1	44.9	1.9	0.05	11.6
		10	15	64.6	2.5	0.03	4.9	45.5	1.5	0.02	2	46.1	1.5	0.04	7.8

	Q [m³/h]	ΔP [Pa]	ti [C°]	Tw 80°/60°C				Tw 60°/40°C				Tw 55°/45°C			
				tu [C°]	P [kW]	Qw [l/s]	ΔPw [kPa]	tu [C°]	P [kW]	Qw [l/s]	ΔPw [kPa]	tu [C°]	P [kW]	Qw [l/s]	ΔPw [kPa]
CWW-H-D 160-3-2,5	355	46	-15	42.9	7.9	0.1	45.1	28.5	5.9	0.07	26.6	29.1	6	0.15	103
		45	-7.5	45.9	7	0.09	36.5	31.2	5.1	0.06	20.2	31.9	5.2	0.13	78.5
		43	0	48.7	6.2	0.08	29	33.9	4.3	5	14.8	34.6	4.4	0.11	58
		41	7.5	51.4	5.5	0.07	22.6	36.3	3.6	0.04	10.4	37.1	3.7	0.09	41
		40	15	53.9	4.7	0.06	17.1	38.6	2.9	0.03	6.7	39.6	3	0.07	27.3
CWW-H-D 200-2-2,5	225	14	-15	35.3	4.3	0.05	9.6	22.2	3.2	0.04	5.5	23.5	3.3	0.08	22.1
		13	-7.5	38.8	3.9	0.05	7.8	25.5	2.8	0.03	4.2	26.9	2.9	0.07	16.9
		13	0	42.2	3.4	0.04	6.2	28.7	2.3	0.03	3	30.2	2.5	0.06	12.5
		13	7.5	45.4	3	0.04	4.8	31.6	1.9	0.02	2.1	33.3	2	0.05	8.8
		12	15	48.5	2.6	0.03	3.6	34.3	1.5	0.02	1.3	36.2	1.6	0.04	5.8
	390	36	-15	25.9	6.1	0.07	18.4	15.1	4.5	0.05	10.6	16.4	4.7	0.11	42.9
		35	-7.5	30.2	5.5	0.07	14.9	19.3	3.9	0.05	8	20.6	4.1	0.1	32.8
		34	0	34.3	4.8	0.06	11.9	23.3	3.3	0.04	5.8	24.6	3.5	0.08	24.2
		33	7.5	38.3	4.2	0.05	9.2	27.1	2.7	0.03	4	28.6	2.9	0.07	17
		32	15	42.3	3.6	0.04	6.9	30.7	2.1	0.03	2.5	32.3	2.3	0.06	11.5
	555	69	-15	20.3	7.5	0.09	27.4	11	5.5	0.07	15.6	12.2	5.8	0.14	64.1
		67	-7.5	20.3	7.5	0.09	27.4	15.6	4.8	0.06	11.8	16.8	5	0.12	48.9
		65	0	29.7	5.9	0.07	17.6	20	4	0.05	8.5	21.3	4.3	0.1	36.1
		63	7.5	34.1	5.2	0.06	13.6	24.4	3.3	0.04	5.8	25.7	3.6	0.09	25.4
		61	15	38.5	4.5	0.05	10.2	28.5	2.6	0.03	3.7	30	2.9	0.07	16.7
CWW-H-D 250-3-2,5	225	8	-15	61.4	6.6	0.08	7.1	42.7	5	0.06	4.3	42.6	4.9	0.12	15.9
		8	-7.5	62.7	5.9	0.07	5.8	43.9	4.3	0.05	3.3	43.8	4.3	0.1	12.1
		8	0	64	5.2	0.06	4.6	44.9	3.7	0.04	2.4	45	3.7	0.09	9
		8	7.5	65.1	4.6	0.06	3.6	45.7	3	0.04	1.7	46	3	0.07	6.4
		8	15	66.1	3.9	0.05	2.7	46.2	2.4	0.03	1.1	47	2.5	0.06	4.3
	390	19	-15	52.1	10	0.12	15.8	35.5	7.5	0.09	9.5	35.9	7.6	0.18	35.8
		18	-7.5	54.3	8.9	0.11	12.8	37.4	6.5	0.08	7.2	37.9	6.6	0.16	27.3
		18	0	56.3	7.9	0.1	10.2	39.2	5.5	0.07	5.3	39.8	5.6	0.14	20.2
		17	7.5	58.2	7	0.09	8	40.9	4.6	0.06	3.7	41.6	4.7	0.11	14.3
		17	15	59.9	6	0.07	6	42.2	3.6	0.04	2.4	43.2	3.8	0.09	9.6
	555	34	-15	45.7	12.9	0.16	25.6	30.5	9.6	0.12	15.2	31.2	9.8	0.24	58.1
		333	-7.5	48.4	11.5	0.14	20.7	33	8.3	0.1	11.5	33.7	8.5	0.21	44.4
		32	0	50.9	10.2	0.13	16.5	35.3	7.1	0.09	8.5	36.2	7.2	0.18	32.8
		30	7.5	53.3	8.9	0.11	12.8	37.5	5.9	0.07	5.9	38.5	6	0.15	23.2
		29	15	55.6	7.7	0.09	9.7	39.5	4.7	0.06	3.9	40.6	4.9	0.12	15.5
CWW-H-D 250-2-2,5	360	11	-15	37.4	7.2	0.09	5.9	23.6	5.3	0.06	3.4	25.2	5.5	0.13	13.7
		11	-7.5	40.7	6.4	0.08	4.8	26.7	4.6	0.06	2.6	28.3	4.8	0.12	10.4
		10	0	43.9	5.7	0.07	3.8	29.6	3.8	0.05	1.9	31.4	4.1	0.1	7.7
		10	7.5	46.9	5	0.06	3	32.3	3.1	0.04	1.3	34.3	3.4	0.08	5.4
		10	15	49.8	4.3	0.05	2.2	34.7	2.4	0.03	0.8	37	2.7	0.07	3.6
	630	29	-15	27.7	10.3	0.13	11.6	16.4	7.6	0.09	6.6	17.9	7.9	0.19	27
		28	-7.5	31.8	9.2	0.11	9.4	20.3	6.5	0.08	5	21.8	6.9	0.17	20.6
		27	0	35.8	8.1	0.1	7.5	24.1	5.5	0.07	3.6	25.7	5.8	0.14	15.2
		26	7.5	39.6	7.1	0.09	5.8	27.7	4.5	0.05	2.5	29.4	4.9	0.12	10.7
		25	15	43.4	6.1	0.08	4.4	31.1	3.5	0.04	1.5	33	3.9	0.09	7
	900	55	-15	21.9	12.7	0.16	17.4	12.1	9.3	0.11	9.9	13.5	9.8	0.24	40.7
		53	-7.5	26.5	11.4	0.14	14.1	16.5	8	0.1	7.5	18	8.5	0.21	31.1
		52	0	31	10.1	0.12	11.2	20.8	6.8	0.08	5.4	22.3	7.3	0.18	22.9
		50	7.5	35.3	8.8	0.11	8.7	25	5.5	0.07	3.7	26.5	6	0.15	16.1
		49	15	39.5	7.6	0.09	6.5	28.9	4.3	0.05	2.3	30.7	4.8	0.12	10.6
CWW-H-D 315-3-2,5	360	9	-15	61.5	10.5	0.13	8.6	42.9	8	0.1	5.2	42.6	7.9	0.19	19.1
		8	-7.5	62.8	9.4	0.12	6.9	44	6.9	0.08	4	43.8	6.9	0.17	14.5
		8	0	64.1	8.3	0.1	5.5	45.1	5.9	0.07	2.9	45	5.9	0.14	10.8
		8	7.5	65.2	7.3	0.09	4.3	45.9	4.9	0.06	2.1	46.1	4.9	0.12	7.7
		8	15	66.2	6.3	0.08	3.3	46.4	3.9	0.05	1.4	47	4	0.1	5.1
	630	19	-15	52	16.1	0.2	19.2	35.4	12.1	0.15	11.5	35.8	12.2	0.3	43.4
		19	-7.5	54.2	14.4	0.18	15.6	37.4	10.5	0.13	8.8	37.8	10.6	0.26	33.1
		18	0	56.2	12.8	0.16	12.4	39.2	8.9	0.11	6.5	39.8	9	0.22	24.5
		18	7.5	58.1	11.2	0.14	9.7	40.9	7.4	0.09	4.6	41.6	7.5	0.18	17.4
		17	15	59.9	9.7	0.12	7.3	42.3	5.9	0.07	3	43.2	6.1	0.15	11.6
	900	35	-15	45.5	20.8	0.26	31.2	30.4	15.6	0.19	18.5	31	15.8	0.38	70.9
		34	-7.5	48.2	18.6	0.23	25.2	32.9	13.5	0.16	14.1	33.6	13.7	0.33	54.1
		33	0	50.8	16.5	0.2	20.1	35.3	11.5	0.14	10.4	36	11.7	0.28	40.1
		31	7.5	53.2	14.5	0.18	15.7	37.5	9.5	0.12	7.3	38.4	9.8	0.24	28.4
		30	15	55.5	12.5	0.15	11.9	39.5	7.6	0.09	4.7	40.6	7.9	0.19	18.9
CWW-H-D 315-2-2,5	560	11	-15	38	11.3	0.14	7.2	24.1	8.4	0.1	4.2	25.6	8.7	0.21	16.6
		10	-7.5	41.3	10.1	0.12	5.8	27.2	7.2	0.09	3.2	28.7	7.5	0.18	12.7
		10	0	44.4	9	0.11	4.6	30.1	6.1	0.07	2.3	31.7	6.4	0.13	9.4
		10	7.5	47.4	7.9	0.1	3.6	32.7	5	0.06	1.6	34.6	5.3	0.13	6.6
		10	15	50.2	6.8	0.08	2.7	35.1	3.9	0.05	1	37.3	4.3	0.1	4.3
	985	27	-15	28.1	16.2	0.2	14.3	16.8	12	0.15	8.2	18.2	12.5	0.3	33.2
		26	-7.5	32.2	14.5	0.18	11.6	20.7	10.3	0.13	6.2	22.1	10.8	0.26	25.3
		26	0	36.2	12.9	0.16	9.2	24.4	8.7	0.11	4.5	26	9.2	0.22	18.7
		25	7.5	40	11.3	0.14	7.1	28	7.1	0.09	3.1	29.7	7.7	0.19	13.1
		24	15	43.7	9.7	0.12	5.4	31.4	5.5	0.07	1.9	33.3	6.2	0.15	8.7
	1410	53	-15	22.3	20.1	0.25	21.4	12.4	14.8	0.18	12.2	13.8	15.5	0.38	50.1
		52	-7.5	26.9	18	0.22	17.4	16.8	12.7	0.15	9.2	18.2	13.5	0.33	38.3
		50	0	31.3	15.9	0.2	13.8	21.1	10.7	0.13	6.7	22.5	11.5	0.28	28.2
		48	7.5	35.6	14	0.17	10.7	25.2	8.8	0.11	4.6	26.7	9.5	0.23	19.9
		47	15	39.8	12	0.15	8	29.2	6.9	0.08	2.9	30.8	7.7	0.19	13.1
CWW-H-D 315-3-2,5	560	9	-15	60.7	16.2	0.2	13	42.3	12.3	0.15	7.9	42	12.2	0.3	29.1
		9	-7.5	62.1	14.5	0.18	10.5	43.6	10.6	0.13	6	43.3	10.6	0.26	22.2
		9	0	63.4	12.8	0.16	8.4	44.7	9	0.11	4.5	44.6	9	0.22	16.4
		9	7.5	64.6	11.3	0.14	6.5	45.7	7.5	0.09	3.2	45.7	7.5	0.18	11.7
		8	15	65.7	9.7	0.12	5	46.4	6	0.07	2.1	46.8	6.1	0.15	7.8
	985	22	-15	51	24.8	0.3	29.4	34.7	18.7	0.23	17.6	35	18.8	0.46	66.4
		21	-7.5	53.2	22.2	0.27	23.8	36.8	16.2	0.2	13.4	37.2	16.3	0.4	50.7
		20	0	55.4	19.7	0.24	18.9	38.7	13.8	0.17	9.9	39.2	13.9	0.34	37.5
		20	7.5	57.4	17.3	0.21	14.8	40.5	11.4	0.14	6.9	41.1	11.6	0.28	26.6
		19	15	59.2	14.9	0.18	11.2	42.1	9.1	0.11	4.6	42.8	9.4	0.23	17.7

	Q [m³/h]	ΔP [Pa]	ti [C°]	Tw 80°/60°C				Tw 60°/40°C				Tw 55°/45°C			
				tu [C°]	P [kW]	Qw [l/s]	ΔPw [kPa]	tu [C°]	P [kW]	Qw [l/s]	ΔPw [kPa]	tu [C°]	P [kW]	Qw [l/s]	ΔPw [kPa]
CWW-H-D 315-3-2,5	1410	40	-15	44.3	32	0.39	47.6	29.6	24	0.29	28.2	30.1	24.3	0.59	108.5
		39	-7.5	47.2	28.6	0.35	38.5	32.2	20.8	0.25	21.5	32.8	21.1	0.51	82.7
		37	0	49.9	25.4	0.31	30.7	34.7	17.7	0.22	15.8	35.4	18	0.44	61.2
		36	7.5	52.4	22.3	0.27	23.9	37.1	14.7	0.18	11.1	37.8	15	0.36	43.3
		35	15	54.8	19.2	0.24	18.1	39.2	11.7	0.14	7.3	40.1	12.1	0.29	28.9
CWW-H-D 400-2-2,5	900	12	-15	36.5	17.7	0.22	11.9	23.1	13.1	0.16	6.9	24.5	13.6	0.33	27.4
		12	-7.5	39.9	15.9	0.19	9.6	26.3	11.3	0.14	5.2	27.7	11.8	0.29	20.9
		12	0	43.2	14	0.17	7.7	29.4	9.6	0.12	3.8	30.9	10	0.24	15.4
		11	7.5	46.3	12.3	0.15	5.9	32.3	7.8	0.1	2.6	33.9	8.3	0.2	10.9
		11	15	49.3	10.6	0.13	4.5	34.9	6.1	0.07	1.6	36.7	6.7	0.16	7.2
	1590	33	-15	26.7	25.3	0.31	23.5	15.8	18.7	0.23	13.5	17.1	19.5	0.47	54.8
		32	-7.5	30.9	22.7	0.28	19.1	19.8	16.1	0.2	10.2	21.1	16.9	0.41	41.8
		31	0	35	20.1	0.25	15.1	23.7	13.6	0.17	7.4	25.1	14.4	0.35	30.8
		30	7.5	39	17.6	0.22	11.7	27.5	11.2	0.14	5.1	29	12	0.29	21.7
		29	15	42.8	15.1	0.19	8.8	31.1	8.8	0.11	3.2	32.7	9.6	0.23	14.3
	2280	65	-15	20.9	31.3	0.38	35.4	11.5	23	0.28	20.1	12.7	24.1	0.59	82.8
		63	-7.5	25.6	28	0.34	28.6	16	19.9	0.24	15.2	17.3	21	0.51	63.1
		61	0	30.2	24.9	0.31	22.7	20.4	16.8	0.2	11	21.7	17.9	0.43	46.5
		59	7.5	34.6	21.8	0.27	17.6	24.7	13.8	0.17	7.6	26.1	14.9	0.36	32.7
		57	15	39	18.7	0.23	13.2	28.8	10.8	0.13	4.8	30.3	11.9	0.29	21.5
CWW-H-D 400-3-2,5	900	11	-15	58.6	25.3	0.31	18	40.6	19.1	0.23	10.7	40.5	19.1	0.46	40.4
		11	-7.5	60.2	22.6	0.28	14.5	42.1	16.6	0.2	8.2	42	16.6	0.4	30.7
		11	0	61.7	20.1	0.25	11.5	43.3	14.1	0.17	6	43.4	14.1	0.34	22.6
		10	7.5	63.1	17.6	0.22	9	44.4	11.7	0.14	4.2	44.7	11.8	0.29	16
		10	15	64.3	15.2	0.19	6.8	45.3	9.3	0.11	2.8	45.9	9.5	0.23	10.7
	1590	26	-15	48.6	38.6	0.47	40.6	32.8	29	0.35	23.9	33.3	29.3	0.71	92.4
		25	-7.5	51.1	34.6	0.42	32.8	35.1	25.1	0.31	18.1	35.6	25.5	0.62	70.3
		25	0	53.4	30.7	0.38	26	37.2	21.4	0.26	13.3	37.8	21.7	0.53	51.8
		24	7.5	55.6	26.9	0.33	20.2	39.2	17.7	0.22	9.3	39.9	18.1	0.44	36.5
		23	15	57.6	23.2	0.29	15.3	40.9	14.1	0.17	6	41.8	14.6	0.35	24.2
	2280	51	-15	41.9	49.5	0.61	65.8	27.6	37.1	0.45	38.3	28.3	37.8	0.92	150.7
		49	-7.5	44.9	44.4	0.54	53.1	30.5	32.1	0.39	29	31.2	32.8	0.8	114.6
		47	0	47.8	39.4	0.48	42.1	33.2	27.3	0.33	21.2	34	28	0.68	84.4
		45	7.5	50.5	34.5	0.42	32.7	35.7	22.6	0.27	14.8	36.6	23.3	0.57	59.5
		44	15	53.1	29.8	0.37	24.7	38	18	0.22	9.6	39.1	18.8	0.46	39.4
CWW-H-D 500-2-2,5	1400	14	-15	34.8	26.6	0.33	16.9	21.8	19.7	0.24	9.5	23.2	20.4	0.5	39.1
		14	-7.5	38.4	23.8	0.29	13.6	25.1	17	0.21	7.2	26.6	17.7	0.43	29.7
		13	0	41.8	21.1	0.26	10.8	28.3	14.3	0.17	5.2	29.9	15.1	0.37	21.8
		13	7.5	45	18.5	0.23	8.3	31.3	11.7	0.14	3.5	33	12.5	0.3	15.2
		13	15	48.1	15.9	0.2	6.2	34	9.1	0.11	2.2	36	10.1	0.24	10
	2450	38	-15	25.3	37.7	0.46	33	14.6	27.8	0.34	18.5	16	29	0.7	77.3
		37	-7.5	29.6	33.7	0.41	26.7	18.8	23.9	0.29	13.9	20.2	25.2	0.61	58.8
		36	0	33.8	29.9	0.37	21.1	22.8	20.2	0.25	10	24.3	21.5	0.52	43.1
		35	7.5	37.9	26.2	0.32	16.3	26.7	16.5	0.2	6.8	28.2	17.9	0.43	30.2
		33	15	41.8	22.5	0.28	12.2	30.4	12.9	0.16	4.3	32.1	14.3	0.35	19.7
	3500	74	-15	19.7	46.4	0.57	49.4	10.5	34.1	0.41	27.5	11.8	35.8	0.87	116.3
		71	-7.5	24.5	41.5	0.51	39.9	15.1	29.4	0.36	20.7	16.4	31.1	0.75	88.4
		69	0	29.1	36.8	0.45	31.5	19.6	24.8	0.3	14.9	21	26.5	0.64	64.9
		67	7.5	33.7	32.2	0.4	24.3	24	20.3	0.25	10.1	25.4	22.1	0.54	45.4
		65	15	38.1	27.7	0.34	18.2	28.2	15.9	0.19	6.3	29.8	17.1	0.43	29.6

Symbolen

Symbols

Qv = luchthoeveelheid

ΔP = drukverlies luchtzijdig

ti = ingaande luchttemperatuur

tu = uitgaande luchttemperatuur

P = vermogen van de batterij

Qw = waterhoeveelheid

ΔPw = drukverlies waterzijdig

Tw = temperatuurtraject water